

INTRODUCING THE ALL-NEW

TVS JUPITER 125 Get more out of your scooter



GET MORE OUT OF YOUR SCOOTER

SUPERIOR PERFORMANCE

POWER & REFINEMENT

Ever since its inception, TVS Jupiter has kept the consumers' needs at the forefront and delivered on its brand philosophy of offering 'MORE' on every count.

Over **4.5 million happy customers** stand testament to this philosophy.

Continuing this focus on meeting the consumers'
evolving needs and offering More, the new TVS Jupiter 125
has been designed with several class-leading features,
which help in taking this philosophy further by offering
GET MORE OUT OF YOUR SCOOTER on every ride.









PREMIUM STYLE

STYLISH & PREMIUM



STYLISH LED HEADLAMP WITH VISOR



ELEGANT TAIL LAMP



DIAMOND-CUT ALLOY WHEELS



BIGGER SPACE

LARGER & MORE CONVENIENT



LARGEST UNDERSEAT STORAGE SPACEBigger-than-ever storage space of 33 L that can comfortably fit two helmets





SOLID SAFETY

HELPING YOU STAY SAFE IN ALL YOUR JOURNEYS




VERSATILE CONVENIENCE

FOR ALL YOUR JOURNEYS - SHORT OR LONG



ADVANCED DIGITAL SPEEDOMETER

Mileage performance indicators help with information such as Distance-to-Empty, Average Fuel Efficiency & Low Fuel Indicator



EXTERNAL FUEL FILLING IN FRONT





DYNAMIC COMFORT

RIDING COMFORT UNDER ALL CONDITIONS



LONGEST FLAT SEAT



EASY GROUND REACH The optimum seat height ensures that your legs reach the ground **easily**



ADVANCED TELESCOPIC SUSPENSION



ADJUSTABLE REAR SHOCKS WITH MIG Adjustable rear shocks with 1st in industry Monotube Inverted Gas (MIG) filled shocks for extra cushioning

BODY BALANCE TECHNOLOGY Body Balance Technology helps make the vehicle easier to control and manoeuvre

SPECIFICATIONS

ENGINE

Type Displacement

Bore x Stroke

Fuel Supply System

Air Filter Type Maximum Power

Maximum Torque Transmission Type

ELECTRICALS

Ignition
Battery
Headlamp
Tail Lamp
Starting System

CHASSIS & SUSPENSION

Frame
Dimensions (lxbxh)

Wheelbase

Ground Clearance

Seat Length Kerb Weight Fuel Tank Capacity

Wheels

Front Suspension Telescopic hydraulic

Rear Suspension Monotube Inverted Gas (MIG) filled shock

Alloy

with Spring aid 3-step adjustable

Single cylinder, 4-stroke, Air cooled

ETFI-Fuel injection - Closed loop

124.8cc

53.5 x 55.5 mm

CVT automatic

6.0 kW @ 6500 rpm

10.5 Nm @ 4500 rpm

ECU Controlled ignition

LED with Clear lens with MFR

High rigidity underbone type

Bulb with LED light guide Electric silent start

12V, 4Ah MF battery

1852 x 681 x 1168

163 mm (unladen)

1275 mm

790 mm

108 kg 5.1 L

Paper filter

BRAKES & TYRES

Front 220 mm Disc, 130 mm Drum

Rear 130 mm Drum

Tyre Size (Front & Rear) 90/90-12 54J (tubeless)

COLOURS











