



TVS KING Deluxe With High Power Engine

PAPER FILTER



Effective filtration of dust

DIGITAL FUEL GAUGE



Clear indication of fuel levels

VENTILATED TAIL DOOR



Better cooling of engine

DRIVER FOOTREST



More comfort for the driver

**Optional accessory - Designer wheel cap. Conditions apply.*

TVS
KING
DELUXE

TVS

TECHNICAL SPECIFICATIONS - TVS KING GS+

ENGINE

Type	4 Stroke, Single Cylinder Forced Air Cooled, Spark Ignition (SI) Engine
Displacement	199.26 cc
Max Power	7.5 kW @ 5500 rpm
Max Torque	15.5 Nm @ 3250 rpm
Bore x Stroke	62 mm x 66 mm
Compression Ratio	9.6 ± 0.3 : 1
Engine Idling rpm	1200 ± 100 rpm
Starting	Electric & Hand Start
Ignition	DC Digital TCI
Fuel feed System	UVD 18 Side Draft Carburetor - Intake & Exhaust Valve Mechanism
Lubrication	Forced wet sump
Magneto	12 V, 180 W @ 5000 rpm

TRANSMISSION

Type	4 Forward & 1 Reverse speed, Constant Mesh Fork and Cam Type Shift mechanism
------	--

CHASSIS

Type	Semi Monocoque
------	----------------

SUSPENSION

Front & Rear	Trailing Arm Type Constant Rate Coil Spring with Co-Axial Hydraulic Damper
--------------	--

BRAKES

Front & Rear	Hydraulic, Drum & Automatic Adjuster Type
--------------	---

WHEELS & TYRES

Rim size front & rear	3.00 D x 8
Tyre size front & rear	4.0 - 8, 6 PR
Tyre pressure front UL/L	30 PSI / 30 PSI
Tyre pressure rear UL/L	30 PSI / 34 PSI

ELECTRICAL

Battery	12 V, 32 Ah
Head lamp	12 V, 35/35 W x 2, Twin head lamp
Tail / Stop lamp	12 V, 21/5 W x 2
Turn signal lamp	12 V, 10 W x 4
Reverse lamp	12 V, 21 W x 1
Warning lamp	Low oil pressure & low fuel
Horn	12 V DC

DIMENSIONS & WEIGHTS

Wheel base	1985 mm
Wheel track	1150 mm
Overall length	2647 mm
Overall width	1329 mm
Overall height	1740 mm
Kerb weight	347 Kg
Max laden weight	677 Kg
Ground clearance	194 mm (Unladen) / 165 mm (Laden)

FUEL TANK CAPACITY

Petrol	7.5 ± 0.5 liters
--------	------------------

GRADEABILITY

Max Gradeability	10°
------------------	-----

TVS Motor Company Ltd.

Post Box No. 4 Harita, Hosur - 635 109. Tel : 04344-276780. Fax: 04344-276878. www.tvsmotor.com