

For more information please contact:

HEAVY DUTY TRACTOR RANGE



THE NEW FACE OF POWER & MILEAGE

THAN OTHERS
Trolley
mum speed – Works faster ures more savings
ley pipe - Unloads the trolley ime and saves time
e platform – Ensures comfort er working hours
Field
m torque – For uniform & ep ploughing
gine – Powerful performance re pulling power
PM –For diesel saving
le in e

Note: Above details are as per respective CFMTTI Budni reports / web information from manufacturers. Data for strictly internal usage only.

MANUFACTURED IN THE WORLD NO.1 PLANT **FEATURES**























MM-18 SPECIFICATION

	Model	MM 18
	Drive	2WD
1	Engine	4 Stroke, Direct Injection, Water Cooled, Diesel Engine
	No of Cylinder/ Displacement	1 / 863.5 cc
	H.P. Category	18 - 20
	Rated Engine Speed	2300
	Transmission Type	6F + 2R
	Speed Range km/h	Forward -1.92 to 28.21 , Reverse- 2.78 to 12.23
	PTO	540
	Clutch Type	Single Clutch
	Brakes	OIB
	Steering Type	Mechanical
	Wheel Base	1470 mm
	Lifting Capacity	750 kg
	Front Tyre	133.35mm - 355.6mm (5.25-14)
	Rear Tyre	203.2mm - 457.2mm (8.0-18)



